

exit from a surface of said multilayer structure at different angles in accordance with the wavelengths.

27. A polarization separating apparatus comprising an optical device constituted by a periodic multilayer structure as defined in Claim 14, means for making a mixture of various luminous flux having a plurality of wavelengths incident on an end surface of said multilayer structure of said optical device, and means for detecting beam rays made to exit from a surface of said multilayer structure at different angles in accordance with polarized beam components.

REMARKS

The amendment avoids multiple dependent claim language and does not introduce new matter.


Please proceed to examination on the merits.

Respectfully submitted,

Michael E. Whitham Reg. No. 32,635

McGuireWoods LLP 1750 Tysons Boulevard Suite 1800 McLean, VA 22102-4215

703-712-5000



Claim 18 (once amended). An optical device according to Claim 14 [or 17], wherein said coupled band is a second coupled band from a lowest-order band.

Claim 19 (once amended). An optical device according to Claim 14 [or 17], wherein a condition given by an expression:

 $\cos 60^{\circ} \le k_s \cdot \lambda_o / (2\pi \cdot n_s) \le \cos 20^{\circ}$ is satisfied.

Claim 20 (once amended). An optical device according to Claim 14 [or 17], wherein said k, satisfies a condition:


 $0.9k_1/m \le k_s \le 1.1k_1/m$ (m is an integer not smaller than 2) when k_1 is a magnitude of a wave vector of the lowest-order coupled band.

Claim 21 (once amended). An optical device according to Claim 14 [or 17], wherein said medium tangent to said surface of said multilayer structure provided as said beam incidence surface or as said beam exit surface is air or vacuum.

Claim 22 (once amended). An optical device according to Claim 14 [or 17], wherein: said periodic multilayer structure is an optical multilayer film in which one structure formed on a transparent substrate is repeated periodically with respect to a wavelength used; and

a surface of said multilayer film tangent to said substrate is provided as said beam incidence surface or as said beam exit surface.

Claim 23 (once amended). An optical device according to Claim 14 [or 17], wherein said one period in said periodic multilayer structure is constituted by layers formed out of difference materials.



Claim 25 (once amended). An optical device according to Claim 14 [or 17], wherein a ratio of a maximum refractive index of a plurality of materials constituting said periodic multilayer structure is not smaller than 1.1 in a wavelength used.

Claim 26 (once amended). A spectroscopic apparatus comprising an optical device constituted by a periodic multilayer structure as defined in Claim 14 [or 17], means for making a mixture of various luminous flux having a plurality of wavelengths incident on an end surface of said multilayer structure of said optical device, and means for detecting beam rays made to exit from a surface of said multilayer structure at different angles in accordance with the wavelengths.

Claim 27 (once amended). A polarization separating apparatus comprising an optical device constituted by a periodic multilayer structure as defined in Claim 14 [or 17], means for making a mixture of various luminous flux having a plurality of wavelengths incident on an end surface of said multilayer structure of said optical device, and means for detecting beam rays made to exit from a surface of said multilayer structure at different angles in accordance with polarized beam components.